

Output Ratings		
Generating Set Model	P135	P150E
380 – 415V, 50 Hz	135 kVA	150 kVA
	108 kW	120 kW
480V, 60 Hz	150 kVA	165 kVA
	120 kW	132 kW

Ratings at 0.8 pf

Ratings Definitions

Prime Power – Model P135

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Standby Power – Model P150E

These ratings are applicable for supplying continuous electrical power (at variable load) in event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO8528-3).

Technical Data		
Engine Model:	Perkins 1006TAG	
Alternator Model:	LL3014F	
Number of Cylinders:	6 in line	
Cubic Capacity: Litres (cu.in)	5.99 (365)	
Bore/Stroke: mm (in)	100.0 (3.94)/127.0 (5.00)	
Compression ratio:	17.0:1	
Aspiration:	Turbocharged, AA Charge Cooled	
Frequency:	50 Hz	60 Hz
Engine Speed:	1500 RPM	1800 RPM
Gross Engine Power: kW (hp)	141 (188)	159 (212)
BMEP: kPA (psi)	1964 (285)	1836 (266)
Piston Speed: m/sec (ft/sec)	6.35 (20.8)	7.62 (25.0)
Fuel Tank Capacity: Litres (US Gal)	300 (79.3)	300 (79.3)
Fuel Consump, P135: 1/hr (USg/hr)	31.2 (8.2)	38.2 (10.1)
Fuel Consump, P150E: 1/hr (USg/hr)	34.4 (9.1)	41.5 (11.0)
Heat Rejection to Exhaust System: kW (Btu/min)	119 (6740)	147 (8367)
Heat Rejection to Cooling System: kW (Btu/min)	69.4 (3947)	76.1 (4329)
Total Radiated Heat: kW (Btu/min)	34.1 (1940)	44.1 (2508)
Exhaust Temperature: °C (°F)	585 (1085)	551 (1024)
Radiator Cooling Air Flow: m ³ /min (cfm)	192 (6780)	246 (8686)
Combustion Air Flow: m ³ /min (cfm)	8.8 (310)	11.2 (396)
Exhaust Gas Flow: m ³ /min (cfm)	25.7 (908)	31.4 (1109)

Note: Standard reference conditions 27°C (80°F) Air Inlet Temp, 152.4m (500ft) A.S.L. 60% relative humidity. All engine performance data based on the above mentioned maximum continuous ratings. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2.

Dimensions and Weights				
Length: mm (in)	Width: mm (in)	Height: mm (in)	Dry: kg (lb)	Wet: kg (lb)
2675 (104.0)	900 (35.4)	1460 (57.5)	1356 (2990)	1400 (3087)
Dry = With Lube Oil		Wet = With Lube Oil and Coolant		

Generating set pictured may include optional accessories



P135 – P150E



FG Wilson (Engineering) Ltd

Old Glenarm Road, Larne, County Antrim BT40 1EJ
Northern Ireland, United Kingdom

Tel: +44 (0) 28 2826 1000 Fax: +44 (0) 28 2826 1111

www.FGWilson.com

